

## Proface X(P)

### Specification:

#### Face Capacity

30,000 (1:N) ;

100,000 (Optional)

#### Palm

5,000 (Customized)

#### Users / Card Capacity

50,000

#### Transaction Capacity

1,000,000 (Optional 2,000,000)

#### User Photo Capacity

30,000

#### Event Photo Capacity

10,000

## Compatibility

Security Relay Box

Wiegand / RS485 Slave Reader with FP / RFID / Barcode / QR-code

Software: ZKBio CVSecurity

Mobile App: ZSmart (Optional)

## Hardware

1GHz Dual Core Customized Computer Vision CPU

1G RAM / 8G Flash

8" (400lux) IPS Touch LCD

125KHz EM Reader / 13.56MHz MF (Optional)

2MP WDR Low Light Camera

Adjustable Light brightness LED

Hi-Fi Voice

Microphone

Distance Detection Sensor

Reset Button and Tamper Switch

## **Access Control Interface**

Lock Relay Output / Alarm Output / Auxiliary Input / Exit Button / Door Sensor

## **Special Function**

IP68 & IK04

0.3s High Speed Face Verification

Live Face detection

Communication Https Encrypted Optional

Event Snapshot

Video intercom

ONVIF Protocol (Compatible with Profile S, Profile T, Profile G, Profile C, Profile Q

& Profile A)

SIP Protocol (Compatible with VT07-B01,Optional)

## **Standard Function**

Access Levels, Groups, Holidays, DST, Duress Mode (Password), Anti-Passback, Record Query, Custom Wallpaper & Screen Saver, Tamper Switch Alarm

## **Communication**

TCP / IP / Wiegand Input / Output / Wi-Fi (Optional) / RS485\* / RS232\*

## **ADDITIONAL INFO**

### **Algorithm**

ZKFace 3.9 & ArmaturaPalm(Customized)

### **Operating Temperature**

-30°C ~ 60°C (-22°F ~ 140°F)

### **Operating Humidity**

≤ 93%

### **Storage Temperature**

-40°C ~ +65°C

### **Storage Humidity**

≤ 93%

## Net Weight

853 g

## Dimension

227 \* 143 \* 26 mm (L\*W\*D)

## POWER

### Operating Voltage

12V DC

### Current Draw

< 2,000 mA